

Impulse Extreme 3.0®

Miller Weldmaster - Impulse Extreme 3.0°

The Impulse Extreme[®] incorporates an effective thermo impulse sealing technology with precision controlled welding parameters that will create the best looking and strongest seams. The Impulse Extreme[®] is ergonomically designed for easy use and operation to improve efficiency.

- Will easily weld pockets AND hems for versatility
- Will weld all seam types required by the sign, awning and blind maker
- · Welds nearly all thermoplastic plastic material for a wide array of products
- PLC controlled heating and cooling cycles for consistent welds
- 10 programmable menu settings for simple operator use
- Water cooled upper and lower welding bars for consistent heat and flat seams
- Available in 12 international languages
- · Complete with any worldwide source, with worldwide service, training and installation

 Advanced dual safety features including safety pressure switch and photo eye monitoring





Overlap Seal



Technical Specifications

Туре	Miller Weldmaster Impulse Extreme 3M
Voltage	50 Amperes- Single Phase- 230 Volts
Air Requirement	140 Liters/Min. at 6.9 Bar
Maximum Temperature	260° C (500°F)
Power Consumption	Approx. 10Kw
Throat Width	3M
Pocket Sizes	13mm to 65mm
Overall Length-Width-Height	3.35m- 1.12m- 1.57m
Weight	NA
Seam Width Available	10mm- 15mm- 20mm- 25mm
Welding Cycle	Approx. 15 Seconds*
Material you can weld	PVC laminated fabrics, Vinyl coated fabrics, Vinyl Films, Polyurethane (PU) coated fabrics, Poly- urethane films, Polypropylene-coated fabrics, Polyethylene (PE), Thermoplastic rubber fabrics, acrylics and others
The Impulse Extreme will produce:	Banners, signs, awnings, simple covers.

*Depending on the application, the seam width and the type of material used