



NESCHEN
HOTLAM 1650 DOUBLEH

ARTICLE NUMBER
 6039986

Presenting the new Neschen HotLam 1650 DoubleH. A real multi-talented laminator that will set new standards in hot encapsulation applications. The DoubleH has enjoyed a fantastic reception from advertising technicians and digital print contractors worldwide during its testing phase.

Designed for professional use, this machine impresses with its high laminating speed and the ability to master even the most challenging hot encapsulation applications. Furthermore, the Neschen HotLam 1650 DoubleH offers a built-in trimmer to cut away overlapping excess media. This is typically used when the laminating film is wider than the substrate being laminated.

NESCHEN HOTLAM 1650 DOUBLEH

- Maximum working speed of 8m/min - For increased productivity
- Two sets of main rollers eliminate the need for a "cooling down" period between hot and cold laminating jobs
- Swing-out Shafts - For easy material loading
- Retractable Trough - For easy feeding of single prints up to 10m long
- Ergonomic and user-friendly Control Panels on the front and rear of the machine - Simplifying single person operation
- Maintenance and repair can mostly be carried out by the users themselves

maximum working width	1650mm
material feed speed	8 m/min.
main rollers maximum pressure	3,1N/mm ² / 450kg
maximum nip (maximum open distance)	40 mm
roller heating	heatable top and bottom roller
max. roller temperature	160 °C

depth (incl. input and output table)	1275 mm
working table height	870mm on wheels 850-950mm on adjustable feet
width (incl. tension control knobs)	2175 mm
height (including wheels)	1390 mm
depth (machine body)	850 mm
machine overall weight (without material)	750 kg
electrical requirements	3P+N/PE400VAC/50Hz-60Hz; 3400W; 32A