



**NESCHEN  
COLDLAM 1650 AND HOTLAM 1650 TH**

**ARTICLE NUMBER**

6037409 ColdLam

6037411 HotLam 1650 TH

**MORE NESCHEN MACHINES AVAILABLE  
FROM 2017**

The first Neschen laminator K600 was presented at Photokina in 1974. We are continuing this success story in 2016!

Neschen laminators are back and better than ever before:

**Designed by Neschen, produced in Europe with additional benefits for our customers worldwide.**

Neschen ColdLam 1650 and Neschen HotLam 1650 TH are our two all-rounders for every application. Not just built for our customers, but with our customers. During the design phase we intensely coordinated the design together with our customers worldwide. Our aim was to build a machine which is practical to use in their everyday work. The designers attached much importance to having maintenance and repair executed by the customers themselves. It's bad for our after sales business, but good for you and your customers.

**NESCHEN COLDLAM 1650**

Neschen ColdLam 1650 is our new laminator for the interesting market segment of signmaking as well as for digital printing service providers. The machine was designed for basic applications and is particularly suitable for mounting and laminating of pressure-sensitive products up to a width of 1,650 mm and offers a flexible overall solution at a reasonable price and with maximum functionality.

- Max. processing speed of 8 m / minute for increased productivity
- Ergonomic, user friendly control panel for easy operation
- Flip-up in-feed table for easy setup
- Pull-out trough for easy feeding of single prints up to 10 m
- Powered rear take up shaft as standard for roll to roll operation

<b>Max. processing width</b>	1650 mm	<b>Depth (incl. feed table)</b>	750 mm
<b>Max. Processing speed</b>	8 m/min.	<b>Table height</b>	870 mm on wheels, adjustable up to 950 mm
<b>Max. contact pressure</b>	1,6N/mm <sup>2</sup>	<b>Net weight</b>	320 kg
<b>Max. substrate thickness</b>	40 mm	<b>Shipping weight</b>	370 kg
<b>Roller heating</b>	Heatable top roller	<b>Shipping dimensions</b>	Width 2300 mm
<b>Max. roller temperature</b>	70 °C		Height 1750 mm
<b>Width</b>	2175 mm		Depth 950 mm
<b>Height</b>	1320 mm	<b>Electrical requirements</b>	1N/PE 230VAC/50-60 Hz;1800W
<b>Depth</b>	550 mm		16A

# "Expertise in Laminating Hardware since 1974"

\* At Photokina 1974 the first Neschen K600 Laminating Machine was launched.

## HOTLAM 1650 TH

Due to its variable pressure and speed adjustments the Neschen HotLam 1650 TH laminator is suitable for new and experienced users who are looking for a particularly powerful laminator, but do not require full encapsulation function. The Neschen HotLam 1650 TH has a technically sophisticated roller system with a high maximum contact pressure. This provides excellent results for each desired application.




Top-speed of 12 m/min for maximum productivity

Swing-out autogrip shaft for easy material loading



Ergonomic, user-friendly control panel for easy operation

Pull-out trough for easy feeding of single prints of up to 10 m



Integrated roll to roll function for higher productivity and less material waste

Additional control panel on the back for easy operation by a single operator



<b>Max. processing width</b>	1650 mm	<b>Depth (incl. feed table)</b>	880 mm
<b>Max. Processing speed</b>	12 m/min.	<b>Table height</b>	870 mm on wheels, adjustable up to 950 mm
<b>Max. contact pressure</b>	3,1N/mm <sup>2</sup>	<b>Net weight</b>	370 kg
<b>Max. substrate thickness</b>	40 mm	<b>Shipping weight</b>	420 kg
<b>Roller heating</b>	Heatable top roller	<b>Shipping dimensions</b>	Width 2300 mm
<b>Max. roller temperature</b>	160 °C		Height 1750 mm
<b>Width</b>	2175 mm		Depth 950 mm
<b>Height</b>	1320 mm	<b>Electrical requirements</b>	1N/PE 230VAC/50-60 Hz; 1800W
<b>Depth</b>	650 mm		