

Print DTF transfers with TexJet® DTG printers

YOU JUST NEED

- DTF Xpress Transfer Films (100 sheet package) to print on with your TexJet® DTG printer.
- DTF Xpress Adhesive Powder (1kg).
- DTF Xpress Antislip Pad.
- Perform a driver update on your Cadlink RIP software.







COMPATIBLE WITH







 $(\mathbf{1})$

BEFORE PRINTING

- 1. Select DTF transfer mode in your RIP sofware. Your image will be automatically mirrored.
- 2. Place the DTF Xpress Antislip Pad on the platen. Place on top, the DTF Xpress Transfer Film with the matte side facing upwards. Alternatively, you can use masking tape to secure the film.



PRINTING

Print your design on **DTF Xpress Transfer** Film. CMYK colors will be printed first, a white top layer will follow.





TRANSFERING PRINT ON GARMENTS

e Only 1440x1440 HS

e Only 1440x720 HS nk Only Greyscale Production

- 1. Transfer the design onto a garment with a heat press.
- 2. **Remove** the film from the garment, once it



APPLYING & ACTIVATING ADHESIVE POWDER

- 1. Apply the DTF Xpress Adhesive Powder on the printed film.
- 2. **Shake off** the excess powder.
- 3. "Bake" the film to melt the DTF Xpress Adhesive Powder, using a heat press or oven. When using a heat press hover over the film.







